



| | |
|--------------------------|--|
| Designed for: | Attaching Hardware to Reinforced Profile |
| Head Style: | Countersunk |
| Drive Bit: | PH2 |
| Thread Form: | Metric |
| Point: | Drill Point |
| Coating: | Electroplated Yellow or Zinc plus Passivation |
| Salt Spray Testing: | Minimum 250 Hours in accordance with BS EN 9227:2012 |
| Corrosion Protection: | Grade 4 acc. to BS EN 1670:2007 |
| Shank Material: | Carbon Steel |
| Material Grade: | AISI C1022 |
| Effective Thread Length: | Fully Threaded |

| Product Code | Size – Shank x NL | HD | Box Quantity |
|---------------------|-------------------|-----------------|--------------|
| CMR 4.0 x 11 Y | 4.0mm x 11.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 16 Y | 4.0mm x 16.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 19 Y or Z | 4.0mm x 19.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 22 Y or Z | 4.0mm x 22.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 25 Y or Z | 4.0mm x 25.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 32 Y or Z | 4.0mm x 32.0mm | 7.25mm ± 0.25mm | 1000 |
| CMR 4.0 x 38 Y or Z | 4.0mm x 38.0mm | 7.25mm ± 0.25mm | 1000 |



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

